

Ready-to-use Modified Asphalt Mixture

RockHard β

Modified asphalt is a product obtained by adding modifiers such as resin and elastomer to regular asphalt, or modified by blowing.

At normal temperature "ready-to-use" mixture is made for the purpose of small scale paving, such as emergency road repair, which can be used At normal temperature without heating.

Rock hard β is our standard type, it is a product that many customers love.

Product Highlights

- Easy compaction: can use car tire to roll the surface
- Can be applied over wet surface
- Have a long shelf life
- High quality mixture using fine aggregate and formula

How to use


step 1

Place mixture into the cracked gap or areas needed repair



step 2

Even the surface with shovel (it will sunk when applied pressure. So make sure to fill extra



step 3

Press and compact the area by rolling with a car or metal plate.



Use:

Road repair such as pothole and touch up

Aggregate grain size:

5mm~10mm

amount to use

Contains 1.6cm × thickness 1m² by 25kg

Related products:

Road Master fine grain (for thin layer)

Easy to open !



Packing:

- 15kg
- 20kg
- 25kg
- 30kg

※ During summer when ground temperature is high, please cover surface with sand or stone dust

※ Surface preparation (spray emulsion and clean) is recommended for higher durability.

Manufacturer LifeductCOMPANY.inc

32-1, Sanda, Atsugi-shi, Kanagawa, 243-0211, Japan

TEL : 046-243-3032 FAX : 046-242-3029

HP : <http://www.lifeduct.co.jp> E-mail : info@lifeduct.co.jp